

JB1113N

General Purpose Dispenser



A popular analog dispenser series featuring dual 110/220V operation. An all-purpose dispenser, versatile and easy to use in a few simple steps – hook up the barrel adapter assembly (selection included) - connect the air and power - set the timer - load the barrel with material - set the air regulator – press the foot switch and start dispensing.

Suitable for all types of fluids, includes a suck-back feature to ensure low viscosity liquids do not drip. Timing interval from 0.01 to 31 seconds.

Features

- Dispense timer
- Wide range of applications
- Barrel suck-back ensures no dripping
- Low-cost system with high reliability

Sales & Support

Fisnar
Global Headquarters
Tel: 1 (973) 646-5044
www.fisnar.com

Fisnar Europe
European Headquarters
Tel: +00 44 (0) 1355 577 222
www.fisnareurope.co.uk

Fisnar Asia
Asia Headquarters
Tel: 852-2389-2827
www.fisnareurope.co.uk

Specifications

Dispense time:	0.01 - 31 seconds
Cycle:	momentary or continuous
Air Input:	70 - 100 psi
Air Output:	1 - 100 psi
Internal voltage:	24 VDC
Voltage:	100 - 240 VAC
Dimensions (WxDxH):	8.63" x 8.50" x 2.63"
Weight:	3.5 lbs.
Standards:	CE, RoHS Compliant