

SUPERFORM/A

SUPERFORM/A is a machine made for cutting and bending axial taped components, it is extremely compact and sturdy and its main characteristic is to form components with rheophore up to 1.4 mm
Its tracking wheels are adjustable independently to allow rapid setup at different forms.

Production rate:

up to 40000 pcs/hr

7915.030

7915.031

7915.180

7915.185


Motor unit for SUPERFORM, 230V - 50/60Hz

Motor unit for SUPERFORM, 115V - 50/60Hz

CS10 feeder for loose axial components

Tape reel holder arm BR6

mod.	version	B		P		C		D		d		L	quick setting
		min	max	min	max	min	max	min	max	min	max		
7915.100A	standard model	4	13	6.5	60 (40*)	1.2	16	0.4	1.3	0.4	1.3	50	7915.100AR
7915.100D	reinforced bending knives	5	13	10.5	60 (40*)	2.4	16	0.6	1.4	0.6	1.4	50	7915.100DR
7915.100F	reduced cutting length reduced bending length	4	13	5	60 (40*)	0.8	10	0.4	0.8	0.4	0.8	50	7915.100FR
7915.100G	like "F" + fixed pitch	4	10	5	-	0.5	4	0.4	0.6	0.4	0.6	3.5	



(*) maximum P dimension with quick setting

SUPERFORM/AP

SUPERFORM/AP is a machine made for cutting and bending axial taped components for vertical assembling, and shaping a little curl on each lead. The machine handles wire diameters ranging from 1 mm to 1.4mm.

By replacing the 2 "cutting/forming wheels" with 2 "only cutting wheels" (optional) it is possible to obtain an U-shape without curls.

Production rate:

up to 20000 pcs/hr

7915.030

7915.031

7915.180

7915.185


Motor unit for SUPERFORM, 230V - 50/60Hz

Motor unit for SUPERFORM, 115V - 50/60Hz

CS10 feeder for loose axial components

Tape reel holder arm BR6

mod.	version	z	P		B		C		L	d	D		h	
			fix	min	max	min	max	min			max	min	max	
7915.102A	standard model	3.1	6.5	60	10	14	1.2	10	50	1	1.3	16	7	11
7915.102B	reinforced bending knives	3.1	10.2	60			2.4				1.4			
7915.102C	standard model	3.9	6.5	60			1.2				1.3			
7915.102D	reinforced bending knives	3.9	10.2	60			2.4				1.4			
7915.102E	standard model	5	6.5	60			1.2				1.3			
7915.102F	reinforced bending knives	5	10.2	60			2.4				1.4			



OPTIONAL ACCESSORIES

SUPERFORM MOTOR UNIT

Equipped with manual speed adjustment and automatic torque control for an easy and fast working of the SUPERFORM machine.

The motor unit is supplied only with the machine assembled.

7915.030

230V Motor Unit for SUPERFORM/A-AP-S-V-R-RCP

7915.031

115V Motor Unit for SUPERFORM/A-AP-S-V-R-RCP

7915.032

230V Motor Unit for SUPERFORM/AF-VP

7915.033

115V Motor Unit for SUPERFORM/AF-VP

600.023

Foot switch for 7915.030/031/032/033 motors



SUPERFORM Tape Reel Holder BR6

A tape reel holder arm to be fixed on the left side of Superform, to facilitate unwinding of the tape.

7915.185

BR6 for all SUPERFORM models



BR6